

FLOWMASTER

CONCRETE & PLASTER HOSE



APPLICATION/USE

Application	: Used as a service between pump and nozzle in transporting wet cement, plaster, grout & concrete
Tube	: Black high abrasion resistant rubber
Reinforcement	: Spiral-plied synthetic fabric with static wire
Cover	: Black abrasion, weather & ozone resistant synthetic rubber
Temperature	-20°F to 176°F (-30°C to 80°C)
Safety Factor	2 : 1
Abrasion loss	<70 mm ³ (DIN 53516)
Branding	FLOWMASTER CONCRETE & PLASTER HOSE 85 BAR

	ID		OD		PRESSURE MAX. WORK		LENGTH STANDART		RADIUS BENDING		APPROX WEIGHT	
PART No.	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUPC03285	1 1/4	32	1.95	50	1215	85	60	200	13	330	0.89	1.33
OMUPC03885	1 1/2	38	2.27	58	1215	85	60	200	15	380	1.16	1.73
OMUPC05185	2	51	2.83	72	1215	85	60	200	20	500	1.59	2.36
OMUPC06385	2 1/2	63	3.43	87	1215	85	60	200	26	650	2.24	3.34
OMUPC07685	3	76	4.06	103	1215	85	60	200	30	750	3.04	4.53
OMUPC08985	3 1/2	89	4.70	119	1215	85	60	200	35	900	3.96	5.90
OMUPC10285	4	102	5.34	136	1215	85	60	200	39	1000	4.99	7.44
OMUPC11485	4 1/2	114	5.89	150	1215	85	60	200	45	1150	5.87	8.75
OMUPC12785	5	127	6.45	164	1215	85	60	200	51	1300	6.70	9.98
OMUPC15285	6	152	7.69	195	1215	85	60	200	59	1500	9.40	14.01

Max diameter available : up to 24"