

FLOWMASTER

CEMENT HOSE 300 PSI



APPLICATION/USE

Application	: Used for the transfer dry or wet material, slurry, and ideal for dry cement, pebble, lime, and other abrasive materials
Tube	: Black high abrasion synthetic rubber
Reinforcement	: Spiral-plied synthetic fabric with helix wire
Cover	: Black abrasion, weather & ozone resistant synthetic rubber
Temperature	-20°F to 176°F (-30°C to 80°C)
Safety Factor	3 : 1
Abrasion Loss	< 70 mm ³ (DIN 53516)
Vacuum	737mmHg / 29inHg
Branding	FLOWMASTER CEMENT HOSE 300 PSI

PART No.	 ID		 OD		 PRESSURE MAX. WORK		 LENGTH STANDART		 RADIUS BENDING		 APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUCSH05120	2	51	2.97	75	300	20	60	200	20	510	2.25	3.35
OMUCSH07620	3	76	4.00	102	300	20	60	200	30	750	3.43	5.12
OMUCSH10220	4	102	5.09	129	300	20	60	200	39	1000	4.81	7.17
OMUCSH12720	5	127	6.02	153	300	20	60	200	49	1250	5.58	8.31
OMUCSH15220	6	152	7.24	184	300	20	30	100	59	1500	8.75	13.04
OMUCSH20420	8	204	9.50	241	300	20	30	100	71	1800	14.10	21.01

Max diameter available : up to 24"