

FLOWMASTER

CEMENT HOSE 150 PSI



APPLICATION/USE

Application	: Recommended for the transfer dry or wet material, slurry, and ideal for dry cement, pebble, lime, and other abrasive
Tube	: Black high abrasion synthetic rubber
Reinforcement	: high tensile textile cords
Cover	: Black abrasion, weather & ozone resistant synthetic rubber
Temperature	-20°F to 176°F (-30°C to 80°C)
Safety Factor	3 : 1
Abrasion Loss	< 70 mm ³ (DIN 53516)
Vacuum	737mmHg / 29inHg
Branding	FLOWMASTER CEMENT HOSE 150 PSI

PART No.	ID		OD		PRESSURE MAX. WORK		LENGTH STANDART		RADIUS BENDING		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUCDH07605	3	76	3.70	94	75	5	60	200	30	750	1.86	2.77
OMUCDH10205	4	102	4.80	122	75	5	60	200	39	1000	2.73	4.07
OMUCDH12705	5	127	5.79	147	75	5	60	200	49	1250	3.34	4.97
OMUCDH15205	6	152	6.82	173	75	5	30	100	59	1500	4.21	6.27
OMUCDH20405	8	204	8.87	225	75	5	30	100	71	1800	5.55	8.28
OMUCDH07610	3	76	3.83	97	150	10	60	200	30	750	2.24	3.34
OMUCDH10210	4	102	4.90	124	150	10	60	200	39	1000	3.10	4.62
OMUCDH12710	5	127	5.88	149	150	10	60	200	49	1250	3.79	5.64
OMUCDH15210	6	152	6.87	174	150	10	30	100	59	1500	4.47	6.66
OMUCDH20410	8	204	9.04	230	150	10	30	100	71	1800	6.82	10.16

Max diameter available : up to 24"