

FLOWMASTER

RADIATOR HOSE



APPLICATION/USE

Application	: Designed with enhanced flexibility in "straight" coolant connection application
Tube	: Black heat resistant synthetic rubber
Reinforcement	: Spiral-plyed synthetic fabric with helix wire
Cover	: Black abrasion, weather & ozone resistant synthetic rubber
Temperature	-20°F to 176°F (-30°C to 80°C)
Safety Factor	4 : 1
Vacuum	737mmHg / 29inHg
Branding	FLOWMASTER RADIATOR HOSE

PART No.	ID		OD		PRESSURE MAX. WORK		LENGTH STANDART		RADIUS BENDING		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMURD01910	3/4	19	1.14	29	150	10	60	200	8	100	0.38	0.50
OMURD01910	1	25	1.38	35	150	10	60	200	10	150	0.40	0.60
OMURD01910	1 1/2	38	1.95	50	150	10	60	200	16	250	0.68	1.01
OMURD01910	1 3/4	45	2.23	57	150	10	60	200	20	250	0.79	1.17
OMURD01910	2	51	2.48	63	150	10	60	200	24	300	0.88	1.31
OMURD01910	3	76	3.50	89	150	10	60	200	30	500	1.40	2.08
OMURD01910	4	102	4.61	117	150	10	60	200	39	700	1.84	2.74
OMURD01910	6	152	6.68	172	150	10	30	100	47	1200	2.55	3.80
OMURD01910	8	203	8.87	225	150	10	30	100	55	1600	3.02	4.50

Max diameter available : up to 24"