

FLOWMASTER

HIGH TEMPERATURE AIR HOSE



APPLICATION/USE

Application	: This hose is specially designed to convey hot air at 300 F (150 c) continuous from the compressor or blower on dry material unloading systems
Tube	: Black heat resistant EPDM rubber
Reinforcement	: high tensile tire cord plies and dual helix wire
Cover	: Black heat, weather & ozone resistant EPDM rubber
Temperature	-20°F to 176°F (-30° C to 80° C)
Safety Factor	4 : 1
Vacuum	737mmHg / 29inHg
Branding	FLOWMASTER HIGH TEMPERATURE AIR HOSE

	ID		OD		PRESSURE MAX. WORK		LENGTH STANDART		RADIUS BENDING		APPROX WEIGHT	
PART No.	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUBL01310	1 / 2	13	1.09	28	150	10	60	200	5	130	0.37	0.55
OMUBL01910	3/4	19	1.46	37	150	10	60	200	8	200	0.62	0.92
OMUBL02510	1	25	1.61	41	150	10	60	200	11	275	0.66	0.98
OMUBL03210	1 1/4	32	1.95	50	150	10	60	200	14	350	0.89	1.32
OMUBL03810	1 1/2	38	2.19	56	150	10	60	200	16	400	1.02	1.52
OMUBL05110	2	51	2.70	69	150	10	60	200	20	500	1.30	1.94
OMUBL06310	2 1/2	63	3.24	82	150	10	60	200	24	600	1.72	3.56

Max diameter available : up to 24"