

FLOWMASTER

DREDGING HOSE



APPLICATION/USE

Application	: Abrasive slurry hose to be used with splift multi coupling it is widely used in the mining industry to handle delivery and suction of dry bulk and slurry
Tube	: Black high abrasion synthetic rubber
Reinforcement	: Spiral-plied synthetic fabric with helix wire
Cover	: extra thick abrasion / weather & ozone resistant cover for durable use. it is bright yellow in color for better visiblty
Temperature	-20°F to 176°F (-30°C to 80°C)
Safety Factor	: 3 : 1
Branding	: FLOWMASTER DREDGING HOSE

PART No.	ID		OD		MAX. WORK PRESSURE		STANDART LENGTH		BENDING RADIUS		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUDRD076	2	51	2.91	74	150	10	60	200	12	300	2.18	3.25
OMUDRD076	3	76	4.04	101	150	10	60	200	20	500	3.46	5.16
OMUDRD102	4	102	5.08	132	150	10	60	200	28	700	5.39	8.04
OMUDRD152	6	152	7.20	184	150	10	30	100	47	1200	9.01	13.43
OMUDRD204	8	204	9.33	238	150	10	30	100	63	1600	12.95	19.30
OMUDRD254	10	254	11.38	294	150	10	12	40	79	2000	20.04	29.86
OMUDRD305	12	305	13.74	353	150	10	12	40	108	2750	29.76	44.34

Max diameter available : up to 24"