

FLOWMASTER

STEAM HOSE



APPLICATION/USE

Application	: Used for steam cleaning, head control service on shipards, chemical plants etc.
Tube	: Black high heat resistant EPDM synthetic rubber.
Reinforcement	: Multi layers of high tensile steel wire braid
Cover	: Red / black heat resistant EPDM syinthetic rubber
Temperature	20°F to 410 F (-30°C to 210°C)
Safety Factor	: 10 : 1
Branding	: FLOWMASTER STEAM HOSE

PART No.	ID		OD		MAX. WORK PRESSURE		STANDART LENGTH		BENDING RADIUS		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUST01318	1 / 2	13	1.02	26	270	18	60	200	5	130	0.32	0.48
OMUST01618	5/8	16	1.13	29	270	18	60	200	8	200	0.37	0.55
OMUST01918	3/4	19	1.25	32	270	18	60	200	10	250	0.42	0.63
OMUST02518	1	25	1.49	38	270	18	60	200	13	320	0.52	0.78
OMUST03218	1 1/4	32	1.76	45	270	18	60	200	15	300	0.64	0.95
OMUST03818	1 1/2	38	2.00	51	270	18	60	200	16	400	0.74	1.10
OMUST05118	2	51	2.64	67	270	18	60	200	20	500	1.22	1.81
OMUST07618	3	76	3.82	95	270	18	60	200	30	750	2.11	3.15

Max diameter available : up to 24"