

FLOWMASTER

HOT TAR & ASPHALT HOSE



APPLICATION/USE

Application	: Specially Designed As Tank Truck or tank wagon hose for loading and unloading Hot Asphalt
Tube	: Black smooth Nitrile rubber and chloroprene Rubber (CR)
Reinforcement	: High tensile tire cord plies and dua helix wire
Cover	: Black abrasion, oil, weather & ozone resistant synthetic rubber
Temperature	-20°F to 410°F (-30°C to 210°C)
Safety Factor	3 : 1
Branding	FLOWMASTER HOT TAR & ASPHALT HOSE

PART No.	ID		OD		PRESSURE MAX. WORK		LENGTH STANDART		RADIUS BENDING		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUGP03810	1 1/2	38	1.89	48	150	10	60	200	10	250	0.74	1.10
OMUGP05110	2	51	2.40	61	150	10	60	200	12	300	0.95	1.41
OMUGP07610	3	76	3.48	88	150	10	60	200	20	500	1.70	3.30
OMUGP10210	4	102	4.61	117	150	10	60	200	28	700	2.82	4.20
OMUGP12710	5	127	5.69	145	150	10	60	200	39	1000	4.16	6.19
OMUGP15210	6	152	6.68	170	150	10	30	100	47	1200	5.09	7.58
OMUGP20410	8	204	8.87	225	150	10	30	100	63	1600	8.21	12.23
OMUGP25410	10	254	10.93	278	150	10	12	40	79	2000	12.47	18.58
OMUGP30510	12	305	13.14	334	150	10	12	40	108	2750	18.60	27.71