

FLOWMASTER

ALUMINA POWDER HOSE



APPLICATION/USE

Aplication	: Recomended for the transfer dry cargo, and special for alumina powder
Tube	: Black high abrasion synthetic rubber
Reinforcement	: high tensile textile cords
Cover	: Black abrasion, weather & ozone resistant synthetic rubber
Temperature	-20°F to 176°F (-30°C to 80°C)
Safety Factor	3 : 1
Abrasion Loss	< 70 mm3 (DIN 53516)
Vacuum	737mmHg / 29inHg
Branding	FLOWMASTER ALUMINA POWDER HOSE

PART No.	ID		OD		PRESSURE MAX. WORK		LENGTH STANDART		RADIUS BENDING		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUCDH07605	3	76	3.70	96	75	5	60	200	30	750	1.86	2.77
OMUCDH10205	4	102	4.80	125	75	5	60	200	39	1000	2.73	4.07
OMUCDH12705	5	127	5.79	149	75	5	60	200	49	1250	3.34	4.97
OMUCDH15205	6	152	6.82	175	75	5	30	100	59	1500	4.21	6.27
OMUCDH20405	8	204	8.87	227	75	5	30	100	71	1800	5.55	8.28
OMUCDH07610	3	76	3.83	99	150	10	60	200	30	750	2.24	3.34
OMUCDH10210	4	102	4.90	126	150	10	60	200	39	1000	3.10	4.62
OMUCDH12710	5	127	5.88	152	150	10	60	200	49	1250	3.79	5.64
OMUCDH15210	6	152	6.87	178	150	10	30	100	59	1500	4.47	6.66
OMUCDH20410	8	204	9.04	234	150	10	30	100	71	1800	6.82	10.16

Max diameter available : up to 24"