

FLOWMASTER

OIL DELIVERY HOSE



APPLICATION/USE

Application	: The industry standard for loading & unloading transfer gasoline, palm oil product and other petroleum base products up to 50 % aromatic content.
Tube	: Black Nitrile synthetic rubber RMA class A (High Oil Resistance)
Reinforcement	: high tensile textile nylon cords
Cover	: Black abrasion, oil, wether & ozone resistant rubber (Flat cover)
Temperature	-20°F to 180F (-30C to 80C)
Branding	FLOWMASTER OIL DELIVERY HOSE WP 250 PSI

PART No.	ID		OD		MAX. WORK PRESSURE		STANDART LENGTH		BENDING RADIUS		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUOSD02517	1	25	1.43	35	250	17	60	200	6	150	0.41	0.62
OMUOSD03217	1 1/4	32	1.73	44	250	17	60	200	8	200	0.51	0.76
OMUOSD03817	1 1/2	38	1.97	53	250	17	60	200	12	300	0.59	0.88
OMUOSD04517	1 3/4	45	2.28	58	250	17	60	200	14	350	0.72	1.08
OMUOSD05117	2	51	2.56	64	250	17	60	200	16	400	0.84	1.25
OMUOSD06317	2 1/2	63	3.03	76	250	17	60	200	18	450	0.99	1.48
OMUOSD07617	3	76	3.62	89	250	17	60	200	20	500	1.25	2.86
OMUOSD08917	3 1/2	89	4.13	104	250	17	60	200	24	600	1.87	2.79
OMUOSD10217	4	102	4.76	120	250	17	60	200	28	700	2.64	3.93
OMUOSD11417	4 1/2	114	5.20	132	250	17	60	200	33	850	2.97	4.43
OMUOSD05117	5	127	5.75	147	250	17	60	200	39	1000	3.81	5.67
OMUOSD06317	6	152	6.85	174	250	17	30	100	47	1200	5.05	7.52
OMUOSD07617	8	204	9.06	230	250	17	30	100	63	1600	11.25	16.77

Max diameter available : up to 24"