

FLOWMASTER

FUEL OIL (DOCK) HOSE



APPLICATION/USE

Application	: Extra durable & thick cover hose for handling petroleum products on marine docks, ships and barges (Bio Diesel, MFO, Crude Oil)
Tube	: Black Nitrile synthetic rubber RMA class A (High Oil Resistance)
Reinforcement	: High tensile and tire cord plies and dual helix wire
Cover	: Black abrasion, oil, wether & ozone resistant rubber (Flat cover)
Temperature	: -20°F to 180F (-30C to 80C)
Safety Factor	: 4 : 1
Branding	: FLOWMASTER DOCK HOSE 300PSI

PART No.	ID		OD		MAX. WORK PRESSURE		STANDART LENGTH		BENDING RADIUS		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUOSD07620	3	76	3.81	97	300	20	60	200	30	750	2.91	4.34
OMUOSD10220	4	102	4.96	126	300	20	60	200	39	1000	4.53	6.76
OMUOSD15220	6	152	7.18	182	300	20	30	100	47	1200	8.26	12.31
OMUOSD20420	8	204	9.48	241	300	20	30	100	63	1600	14.19	21.15
OMUOSD25420	10	254	11.64	296	300	20	12	40	71	1800	18.77	27.96
OMUOSD30520	12	305	14.02	356	300	20	12	40	79	2000	30.90	46.04

Max diameter available : up to 24"