

FLOWMASTER

SLURRY & WASTE HOSE



APPLICATION/USE

Application	: Delivery and suction application is waste water, sawage, mud, etc
Tube	: Black natural rubber blend compound
Reinforcement	: Spiral-plied synthetic fabric with helix wire
Cover	: Black abrasion, weather & ozone resistant synthetic rubber
Temperature	-20°F to 176 F (-30 C to 80 C)
safety factor	: 3 : 1 ° ° °
vacuum	: 737mmHg / 29inHg
Branding	FLOWMASTER WATER SUCTION & DELIVERY HOSE

	 ID		 OD		 PRESSURE MAX. WORK		 LENGTH STANDARD		 RADIUS BENDING		 APPROX WEIGHT	
PART No.	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
OMUWT01910	3/4	19	1.14	29	150	10	60	200	4	100	0.40	0.60
OMUAH02510	1	25	1.38	35	150	10	60	200	6	150	0.50	0.75
OMUAH03210	1 3/4	32	1.65	42	150	10	60	200	8	200	0.64	0.95
OMUAH03810	1 1/2	38	1.89	48	150	10	60	200	10	250	0.74	1.10
OMUAH05110	2	51	2.40	61	150	10	60	200	12	300	0.95	1.41
OMUAH06310	2 1/2	63	2.94	75	150	10	60	200	16	400	1.34	2.53
OMUAH07610	3	76	3.48	88	150	10	60	200	20	500	1.70	3.30
OMUAH08910	3 1/2	89	4.04	103	150	10	60	200	20	500	1.70	3.30
OMUAH10210	4	102	4.61	117	150	10	60	200	28	700	2.82	4.20
OMUAH12710	5	127	5.69	145	150	10	60	200	39	1000	4.16	6.19
OMUAH15210	6	152	6.68	170	150	10	30	100	47	1200	5.09	7.58
OMUAH20410	8	204	8.87	225	150	10	30	100	63	1600	8.21	12.23
OMUAH25410	10	254	10.93	278	150	10	12	40	79	2000	12.47	18.58
OMUAH30510	12	305	13.14	334	150	10	12	40	108	2750	18.60	27.71
OMUAH01920	3/4	19	1.14	29	300	20	60	200	4	100	0.41	0.60
OMUAH02520	1	25	1.43	36	300	20	60	200	6	150	0.57	0.85
OMUAH03220	1 3/4	32	1.70	43	300	20	60	200	8	200	0.72	1.07
OMUAH03820	1 1/2	38	1.94	49	300	20	60	200	10	250	0.83	1.24
OMUAH05120	2	51	2.53	64	300	20	60	200	12	300	1.40	2.09
OMUAH06320	2 1/2	63	3.05	77	300	20	60	200	16	400	1.80	2.68
OMUAH07620	3	76	3.62	92	300	20	60	200	20	500	2.23	3.32
OMUAH08920	3 1/2	89	4.13	105	300	20	60	200	20	500	2.65	3.94
OMUAH10220	4	102	4.71	120	300	20	60	200	28	700	3.36	5.01
OMUAH12720	5	127	5.77	147	300	20	60	200	39	1000	4.57	6.81
OMUAH15220	6	152	6.93	176	300	20	30	100	47	1200	6.73	10.03
OMUAH20420	8	204	9.10	231	300	20	30	100	63	1600	10.22	15.22
OMUAH25420	10	254	11.13	283	300	20	12	40	79	2000	14.58	21.73
OMUAH30520	12	305	13.46	342	300	20	12	40	108	2750	22.54	33.59

Max diameter available : up to 24"