

FLOWMASTER

WATER HOSE



APPLICATION/USE

Application	: Durable water hose with a thick wall to withstand harsh working conditions in mines, construction sites and industries
Tube	: Black natural rubber blend compound
Reinforcement	: High tensile textile cords
Cover	: Black abrasion, weather & ozone resistant synthetic rubber
Temperature	-20°F to 176 F (-30 C to 80 C)
Branding	FLOWMASTER WATER DELIVERY HOSE 150 PSI

PART No.	 ID		 OD		 PRESSURE MAX. WORK		 LENGTH STANDART		 APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	(lbs/ft)	(Kg/m)
OMUWD01910	3/4	19	1.08	27	150	10	60	200	0.29	0.44
OMUWD02510	1	25	1.31	33	150	10	60	200	0.37	0.55
OMUWD03210	1 1/4	32	1.59	40	150	10	60	200	0.46	0.68
OMUWD03810	1 1/2	38	1.83	46	150	10	60	200	0.53	0.80
OMUWD05110	2	51	2.34	59	150	10	60	200	0.70	1.04
OMUWD06310	2 1/2	63	2.81	71	150	10	60	200	0.85	1.27
OMUWD07610	3	76	3.46	88	150	10	60	200	1.37	2.04
OMUWD08910	3 1/2	89	3.98	101	150	10	60	200	1.61	2.40
OMUWD10210	4	102	4.49	114	150	10	60	200	1.85	2.76
OMUWD12710	5	127	5.50	140	150	10	60	200	2.52	3.76
OMUWD15210	6	152	6.49	165	150	10	30	100	3.07	4.58
OMUWD20410	8	204	8.61	219	150	10	30	100	5.24	7.81
OMUWD25410	10	254	10.61	270	150	10	12	40	7.52	11.21
OMUWD30510	12	305	12.70	323	150	10	12	40	11.74	17.50

Max diameter available : up to 24"