

# FLOWMASTER

## SAND BLASTING HOSE



### APPLICATION/USE

|               |                                                                               |
|---------------|-------------------------------------------------------------------------------|
| Application   | : Abrasion resistant hose for-lasting use in sand and steel blasting services |
| Tube          | : Thick black high abrasion resistant rubber                                  |
| Reinforcement | : Spiral-plyed synthetic fabric with static wire                              |
| Cover         | : Black abrasion, weather & ozone resistant synthetic rubber                  |
| Temperature   | -20°F to 176°F (-30 C to 80 C)                                                |
| Safety Factor | 3 : 1                                                                         |
| Vacuum        | <70 mm3 (DIN 53516)                                                           |
| Branding      | FLOWMASTER SANDBLASTING HOSE 150 PSI                                          |

| PART No.   | ID    |    | OD   |    | PRESSURE<br>MAX. WORK |     | LENGTH<br>STANDART |        | RADIUS<br>BENDING |     | APPROX<br>WEIGHT |        |
|------------|-------|----|------|----|-----------------------|-----|--------------------|--------|-------------------|-----|------------------|--------|
|            | in    | mm | in   | mm | psi                   | bar | ( M )              | ( FT ) | in                | mm  | (lbs/ft)         | (Kg/m) |
| OMUSB01310 | 1/2   | 13 | 1.09 | 28 | 150                   | 10  | 60                 | 200    | 5                 | 130 | 0.37             | 0.55   |
| OMUSB01910 | 3/4   | 19 | 1.46 | 37 | 150                   | 10  | 60                 | 200    | 8                 | 200 | 0.62             | 0.92   |
| OMUSB02510 | 1     | 25 | 1.61 | 41 | 150                   | 10  | 60                 | 200    | 11                | 275 | 0.66             | 0.98   |
| OMUSB03210 | 1 1/4 | 32 | 1.95 | 50 | 150                   | 10  | 60                 | 200    | 14                | 350 | 0.89             | 1.32   |
| OMUSB03810 | 1 1/2 | 38 | 2.19 | 56 | 150                   | 10  | 60                 | 200    | 16                | 400 | 1.02             | 1.52   |
| OMUSB05110 | 2     | 51 | 2.70 | 69 | 150                   | 10  | 60                 | 200    | 20                | 500 | 1.30             | 1.94   |
| OMUSB06310 | 2 1/2 | 63 | 3.24 | 82 | 150                   | 10  | 60                 | 200    | 24                | 600 | 1.72             | 3.56   |

Max diameter available : up to 24"